

SpectrULite[®] organics | TECHNICAL INFORMATION

WATER-BORNE ORGANIC COATINGS

INTERMIXABLE COLOR STANDARDS - INTERNATIONAL PRODUCT REFERENCES

PANTONE REFERENCE	COATING COLOR	EUROPEAN PRODUCT COATING REFERENCE		COLOR CONCENTRATE REFERENCE (1)	AMERICAN PRODUCT COATING REFERENCE	
		ACRYLIC SYSTEM 84	EPOXY SYSTEM 95		ACRYLIC SYSTEM 84	EPOXY SYSTEM 95
-	Clear	84-0001	85-0001	-	84-0001	95-001
-	Fast-cure Clear	-	85-0002	-	-	-
-	Frost	84-0010	85-0010	-	84-0000	95-000
Green C	Green	84-1000	85-1000	Green 101	84-6100	95-600
355 C	Light Green	-	85-1001	-	-	-
300 C	Blue- Red Shade	84-2000	85-2000	Blue 201	84-7100	95-700
3005 C	Turquoise blue	84-2001	85-2001	Blue 202	84-7101	-
012 C	Yellow - Red shade	84-3000	85-3000	Yellow 301	84-3100	95-300
355 C	Yellow - Green shade	84-3008	85-3008	Yellow 302	-	-
Black C	Black	84-4000	85-4000	Black 401	84-4100	95-400
-	Black Matt	84-4007	85-4007	-	RD 5624A	95-410
484 C	Brown	84-6001	85-6001	Brown 600	-	-
200 C (2)	Red - Yellow Shade	84-7000	85-7000	Red 701	84-1100	95-100
226 C	Red - Blue Shade	84-7001	85-7001	Red 702	84-1101	95-133
200 C (2)	Red - Yellow Shade	84-7002	85-7002	Red 703	-	-
Rhodamine C	Magenta	84-7016	85-7016	-	-	-
Warm Red C	Orange	84-7300	85-7300	Orange 730	-	-
151 C	Orange -Yellow Shade	84-7301	85-7301	Orange 731	-	-
Violet C	Violet	84-8000	85-8000	Violet 801	84-8100	95-702
-	White	84-9000	85-9000	White 901	84-0003	95-003

1 Color concentrates can be mixed with base coatings to provide further options for on-site color mixing and matching

2 84-7002 is the preferred option for Pantone Ref 200C because of improved transparency and heat stability

3 For transparent colors, recommend to start with 25% of color plus 75% of base clear coating

4 For opaques, add 50% White to 50% of the transparent color mix created as in example above (3)

5 For colored etches, recommend to start with 5% of color plus 95% of base frost coating

IMPORTANT INFORMATION

The following supersedes any provisions in your company's forms, letters and papers. The information and statements contained herein are provided free of charge. They are believed to be accurate at the time of publication. Ferro makes no warranty, whether expressed or implied, including warranties of merchantability or fitness for a particular purpose for these products. No statement or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall Ferro be liable for incidental, consequential or other damages from alleged negligence, breach of warranty, strict liability, contract or any other legal theory, arising out of the use or handling of these products. The sole remedy of the buyer and the sole liability of Ferro for any claim shall be for the buyer's purchase price of the products that are the subject of the claim. Claims not made within thirty (30) days from the delivery date shall be deemed waived. Ferro's liability ceases upon making delivery of the product to carrier at shipping point.