

299B is a fully synthetic glass grinding fluid for use in high-volume automated production lines. 299B features high rates of removal, rapid controlled settling, low energy consumption, and greatly extended wheel wear rates.

Lubricity – 299B features a concentrated lubricity package for removal rates up to 40% higher than those of most competitive fluids.

Lower Power Consumption – Because of its superior lubrication package 299B cuts power requirements by substantially lowering the coefficient of friction at the wheel/glass interface, substantially reducing the amount of power needed.

Extended Wheel Life – 299B significantly extends the life of most diamond wheels while providing a high-quality finish.

Controlled Settling – 299B is formulated with an efficient settling additive package. This package allows the glass fines to settle out of solution in a controlled manner, eliminating build up in return lines and on machine parts. When it is time to clean settling tanks and automatic swarf removal equipment, the residue can be either shoveled out or simply washed out with water.

Biologically Stable – 299B provides excellent resistance to biological deterioration. Each component in the formulation is selected for its resistance to attack by bacteria and fungus. 299B uses no toxic biological control agents that may harm worker's skin or upper respiratory system.

Starting Dilutions – 299B is to be used at a dilution of 50:1 to 100:1 (2%-1%) in water, depending on the severity of the job, wheel type, and required line speed.

Extended Sump Life – Because of new more stringent waste disposal regulations, coolants today must provide longer service life. When managed correctly, 299B can last twice as long as normal coolants. To obtain maximum life from 299B, test for suspended solids once a week. Once solids level has been determined, simple post treatment in the existing tank will clear the fluid of most unwanted glass fines and leave the fluid ready for another week of high-speed operation. To learn more about how to post treat 299B contact your Ferro representative or your distributor.

Automated Dilution Control – 299B can be diluted by several methods. Simple venturi dilution systems work well for smaller users. If more accuracy is required for high-volume users, consider using our Automated Dilution Control Station, which is accurate to one quarter of one percent.

Custom Options – 299B can be custom formulated to meet special performance requirements, such as increased line speeds, extended wheel life, or swarf removal.

Contains No Silicone – 299B contains no silicone, diethanolnitrosamine, nitrites, phosphates, PCBs, PTBBA, mercurial, phenols, or mineral oils.

www.ferro.com

DISCLAIMER: Reasonable care has been taken in the preparation of this information, but **FERRO EXTENDS NO WARRANTIES, MAKES NO REPRESENTATIONS AND ASSUMES NO RESPONSIBILITY AS TO ACCURACY OR SUITABILITY OF THIS INFORMATION OF THIS PRODUCT FOR ANY PURCHASER'S OR USER'S USE OR FOR ANY CONSEQUENCE OF ITS USE. FERRO DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR ANY PARTICULAR USE.** All statements, technical information and recommendations contained herein are based on Seller's or Manufacturer's test and the test of others, and are believed to be accurate, but no guarantee of accuracy is made. Judgment as to the suitability of information herein or the user's purposes are necessarily the user's responsibility. Users shall determine the suitability of the products for their own intended application.

Users assume all risk of use or handling whether or not in accordance with any statements or recommendation of the seller or manufacturer. Liability, if any, is and shall be limited to the replacement of such quantity of material proved not to conform to specifications as set out in product specification. Statements concerning the possible use of these products are not intended as recommendation to use these products in infringement of any patent. No guarantee is made that any use of the products does not infringe third-party intellectual property or patent rights anywhere in the world.

299B Precision Glass Grinding Fluid

Recommended Starting Dilutions

Beveling	50:1 to 100:1
Lens Generating	30:1
Edging	75:1 to 100:1
Surface Grinding	50:1

Typical Properties

Appearance	Transparent Green Liquid
Volatile Component	Water
Freeze Point	32°F
Boiling Point	212°F
pH	9.4 - 9.8
Evaporation Rate	NA
Odor	Mild
Vapor Pressure	NA
Vapor Density	NA
Specific Gravity	1.04 - 1.05
VOC	None
Weight per Gallon	8.65 - 8.75
Solubility in Water	Infinite

Packaging and Handling – 299B is a liquid packed in non-returnable drums, Tote Bins, Pails, and Bulk. Refer to the Material Safety Data Sheet for suitable materials of construction, for handling, and storing of this product. Observe all safety precautions shown on the label and in the Material Safety Data Sheet.

Health	1
Flammability	1
Reactivity	0
Personal Protection	B

Ferro Electronic Material Systems

Penn Yan, New York, U.S.A.

315-227-5276

www.ferro.com

DISCLAIMER: Reasonable care has been taken in the preparation of this information, but **FERRO EXTENDS NO WARRANTIES, MAKES NO REPRESENTATIONS AND ASSUMES NO RESPONSIBILITY AS TO ACCURACY OR SUITABILITY OF THIS INFORMATION OF THIS PRODUCT FOR ANY PURCHASER'S OR USER'S USE OR FOR ANY CONSEQUENCE OF ITS USE. FERRO DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR ANY PARTICULAR USE.** All statements, technical information and recommendations contained herein are based on Seller's or Manufacturer's test and the test of others, and are believed to be accurate, but no guarantee of accuracy is made. Judgment as to the suitability of information herein or the user's purposes are necessarily the user's responsibility. Users shall determine the suitability of the products for their own intended application.

Users assume all risk of use or handling whether or not in accordance with any statements or recommendation of the seller or manufacturer. Liability, if any, is and shall be limited to the replacement of such quantity of material proved not to conform to specifications as set out in product specification. Statements concerning the possible use of these products are not intended as recommendation to use these products in infringement of any patent. No guarantee is made that any use of the products does not infringe third-party intellectual property or patent rights anywhere in the world.