

## FL-40 Water-Based Degreaser

FL-40 removes grease, oil, light asphaltic deposits, diesel residues, and other hard to remove oil and dirt deposits. FL-40 is also effective in removing many deposits containing animal fat and oil residues in combination. It is designed as a heavy duty cleaner where grease, oils, tars, and or fatty deposits need to be removed fast and inexpensively.

FL-40 is widely used as a pressure washing fluid, and can be sprayed or applied on machinery or floors. FL-40 is also useful as an exterior truck and machinery cleaner in machine shops, truck shops, industrial plants, forklift shops, auto dealerships, marine repair, heavy equipment dealers, meat plants, poultry plants, lumber mills, plywood mills, etc.

**Versatility** – FL-40 can be used in pressure washers, brushes, dip tanks, automated spray washing systems, or automated floor scrubbing equipment.

Note: Do not use concentrated FL-40 on aluminum because it can cause discoloration or pitting. Do not allow to dry on glass.

**Highly Dilutable** – Because FL-40 is so concentrated, it can be diluted up to 20:1 with water.

**Waste Treatable** – FL-40 is highly waste treatable and biodegradable. Always dispose of this and all other chemical products according to Federal and State regulations.

**Non-Flammable** – FL-40 is water based and has a flash point above 200°F, making it safe for production or maintenance cleaning operations.

**Paint Compatibility** – When diluted, FL-40 is safe to use on most industrial paint and coatings. Always test compatibility in a small inconspicuous area.

### Recommended Starting Dilutions

Beveling 5:1 to 10:1

### Typical Properties

Appearance	Clear to Yellowish Liquid
Volatile Component	2-Butoxyethanol
Freeze Point	32°F
Boiling Point	212°F
pH	11.0 ± 0.2
Evaporation Rate	NA
Odor	Mild
Vapor Pressure	NA
Vapor Density	NA
Specific Gravity	1.04
VOC	1-10%
Weight per Gallon	8.65
Solubility in Water	Infinite

**Packaging and Handling** – FL-40 is a liquid packed in non-returnable drums. Refer to the Material Safety Data Sheet for suitable materials of construction, for handling, and storing of this product. Observe all safety precautions shown on the label and in the Material Safety Data Sheet.

Ferro Electronic Material Systems Penn Yan, New York, U.S.A. 315-227-5276

[www.ferro.com](http://www.ferro.com)

DISCLAIMER: Reasonable care has been taken in the preparation of this information, but FERRO EXTENDS NO WARRANTIES, MAKES NO REPRESENTATIONS AND ASSUMES NO RESPONSIBILITY AS TO ACCURACY OR SUITABILITY OF THIS INFORMATION OF THIS PRODUCT FOR ANY PURCHASER'S OR USER'S USE OR FOR ANY CONSEQUENCE OF ITS USE. FERRO DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR ANY PARTICULAR USE. All statements, technical information and recommendations contained herein are based on Seller's or Manufacturer's test and the test of others, and are believed to be accurate, but no guarantee of accuracy is made. Judgment as to the suitability of information herein or the user's purposes are necessarily the user's responsibility. Users shall determine the suitability of the products for their own intended application.

Users assume all risk of use or handling whether or not in accordance with any statements or recommendation of the seller or manufacturer. Liability, if any, is and shall be limited to the replacement of such quantity of material proved not to conform to specifications as set out in product specification. Statements concerning the possible use of these products are not intended as recommendation to use these products in infringement of any patent. No guarantee is made that any use of the products does not infringe third-party intellectual property or patent rights anywhere in the world.